



5. For auto-dimming inspection(option)

- 1)Key on the car
- 2)Press key  then led green light will be on
- 3)Keep the mirror with on status
- 4)Using hand or a black paper cover the backside of the mirror (see the picture near)
- 5)After while ,mirror will turn dark automatically
- 6)Take off the backside cover ,then the mirror will turn normal



6. Trouble Shooting

FOR CAMERA DISPLAY FUNCTION ONLY

Q: The Blue Led Never Turns On And I Do Not Get A Picture?

A: Test To Confirm That (+ & -) Are Connected Properly And Fuse Is Good.

Q: The Blue Led Is On But I Do Not Any Picture?

A: Make Sure That The Video Rca's Are Connected Properly And That The Camera Is Powered Up Properly As Per Camera Instructions.

Q: The Image On The Mirror Is Opposite (left Is Right And Right Is Left) What Is Wrong?

A: The **White** Jumper On The Camera Harness Is Connected (should Be Cut In Half).

Q: I DO NOT Like The Parking Lines, How Can I Turn Them Off?

A: Connect The **Green** Jumper At The Camera Harness To Turn The Parking Line Feature Off.

REARVIEW MIRROR MONITOR



Owner's Manual

Replacement Mirror Monitor System

WARNINGS

• **PROFESSIONAL INSTALLATION REQUIRED**

The following instructions are intended for professional installers.

- Dropping your mirror unit or subjecting it to excessive shock and vibrations as this may cause it to malfunction and is not covered by warranty.
- **THE MIRROR IS NOT WATERPROOF.** Avoid exposing it to rain or other forms of excessive moisture. **WATER DAMAGE IS NOT COVERED UNDER THE WARRANTY.**

1. Installation

- 1) Remove existing mirror from vehicle.
- 2) If existing mirror tab is D-tab style mount mirror to windshield and go to step 3. If original mirror is not D-tab style or headliner mount go to step 2a.
- 2a) Locate the supplied D-tab and the rearview mirror adhesive and install on windshield as per adhesive instructions.

Note: DO NOT attempt to remove the existing mirror mount as damage to the windshield may occur.

- 3) Remove the knee bolster on the driver side as well as the A-pillar cover (it may also be necessary to remove the sunvisor and maybe even the overhead console in order to freely route the power harness from the knee bolster to the mirror connector).

- 4) Connect the power harness to the mirror and use supplied mirror harness wire cover in order to neatly route the cable up the windshield to the headliner.

- 5) Reassemble all above covers and make connections at knee bolster.

2. Wiring

ACC+: 12V+ Ignition

GND: Chassis Ground

BACKUP CAR SIGNAL:

- 1) Connect with backup car light
- 2) Synchronizing signal
- 3) Option: switch off auto-dimming function

3. Setup

- 1) Turn Ignition ON
- 2) LED on mirror will turn ON
- 3) If AUX video source was connected (turn video source ON then press PWR button on mirror and the image should appear on screen)
- 4) Shift vehicle into reverse, the camera image will appear on the screen
- 5) Shift vehicle out of reverse and the camera image will disappear and go back to its previous stage

4. Power Button Operation

CAMERA INPUT MODE: Adjust brightness of screen

VIDEO 1 INPUT MODE: Turns ON and OFF LCD

Please note: auto-dimming mirror this button is only working for switch on/off the LED light.