
MONITOR:



- 1. Indicator Light
- 2. R/C Window
- 3. Power
- 4. V1/V2
- 5. Negative Decrease
- 6. Menu
- 7. Positive Increase
- 8. AV IN Jack(Optional)
- 9. Earphone jack(Optional)

CAUTION:


For your safety, please rotate the angle of the display or turn off the display while driving.

SPECIAL STATEMENT:

LCD may have a few bright dots, which is normal for the matrix display technology, and doesn't indicate defects of faults

NOTICE:


- Please operate instruction manual completely before use;
- The unit is manufactured with precision elements pay attention to protection against dampeness;
- Prevent the hard object from scratching LCD surface;
- High voltage inside non-technical authorized person is not allowed to dismantle the unit.



REMOTE CONTROL

- 1. Power
- 2. V1/V2 Change
- 3. Positive Increase
- 4. Menu
- 5. Negative Decrease
- 6. Mode Selection

Connection



MONITOR With Built-in speaker

SPECIFICATIONS:

- Display size: 5.8 inch (16:9)
- Resolution: 400*RGB*234
- Power supply: DC 12V
- Input : Dual video input; One audio input
- System: PAL/NTSC auto switching
 Mode:16:9 and 4:3 auto switching
- Built-in speaker

MONITOR:



- 1. Indicator Light or IR
- 2. R/C Window
- 3. Power
- 4. Mode
- 5. Negative Decrease
- 6. Menu
- 7. Postive Increase
- 8. AV IN Jack (Optional)
- 9. Earphone jack (Optional)

CAUTION:


For your safety, please rotate the angle of the display or turn off the display while driving.

SPECIAL STATEMENT:

LCD may have a few bright dots, which is normal for the matrix display technology, and doesn't indicate defects of faults

NOTICE:


- Please operate instruction manual completely before use;
- The unit is manufactured with precision elements pay attention to protection against dampeness;
- Prevent the hard object from scratching LCD surface;
- High voltage inside non-technical authorized person is not allowed to dismantle the unit.



REMOTE CONTROL

- 1. Power
- 2. V1/V2 Change
- 3. Positive Increase
- 4. Menu
- 5. Negative Decrease
- 6. Mode Selection

Connection



SPECIFICATIONS:

- Display size: 5.8 inch (16:9)
- Resolution: 400*RGB*234
- Power supply: DC 12V
- Input : Dual video input; One audio input(optional)
- System: PAL/NTSC auto switching
- Mode:16:9 and 4:3 auto switching
- Built-in speaker (optional)Dual IR(optional)